

Appl. No. 10/812,527
Amdt Dated Jan. 13, 2006
Reply to Office Action July. 11, 2005

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claim 1 (currently amended): A clip adapted to secure a heat sink to an electronic device, the clip comprising:

a main body comprising a pressing part adapted to press the heat sink to the electronic device, a first leg extending downwardly from one end of the pressing part, and a supporting portion extending from an opposite end of the pressing part, the supporting portion defining a hole therein;

a cam member located above the supporting portion, the cam member comprising a cam and a handle extending from the cam for rotating the cam, and

a buckling piece located below the supporting portion, the buckling piece comprising a connecting part and a second leg extending from the connecting part, ~~the connecting part providing a spring finger; wherein the connecting part moves up through the hole of the supporting portion to pivotally connect with the cam, and the heat sink can be secured to the electronic device by rotating the cam to a locked position from an unlocked position, and the spring finger of the connecting part of the buckling piece is located below the supporting portion at the unlocked position and above the supporting portion at the locked position.~~

Claim 2 (original): The clip of claim 1, wherein two reinforcing ribs extend

Appl. No. 10/812,527
Amdt Dated Jan. 13, 2006
Reply to Office Action July. 11, 2005

downwardly from opposite longitudinal sides of the pressing part.

Claim 3 (original): The clip of claim 2, wherein a vertical thickness of each of the reinforcing ribs tapers from a center thereof to opposite ends thereof respectively.

Claim 4 (previously presented): The clip of claim 1, wherein the first leg of the main body comprises a lower rectangular end, and said end defines an aperture therein.

Claim 5 (previously presented): The clip of claim 1, wherein the second leg of the buckling piece comprises a lower rectangular end, and said end defines an aperture therein.

Claim 6 (previously presented): The clip of claim 1, wherein the cam is substantially bifurcated, with two parallel portions thereof receiving the connecting part of the buckling piece therebetween.

Claim 7 (previously presented): The clip of claim 1, wherein the connecting part of the buckling piece comprises a main plate and two reinforcing ribs extending perpendicularly from opposite longitudinal sides of the main plate respectively, and the spring finger is provided in the main plate.

Claim 8 (currently amended): The clip of claim 7, wherein in the locked

Appl. No. 10/812,527
Amdt Dated Jan. 13, 2006
Reply to Office Action July. 11, 2005

position, the spring finger is located above the supporting portion, whereby the spring finger ~~and~~ protects the pressing part from abruptly restored deformation.

Claim 9 (currently amended): The clip of claim 7, wherein ~~the cam is substantially bifurcated, with two parallel portions thereof receiving the connecting part of the buckling piece therebetween,~~ the cam defines two pivot holes in said parallel portions respectively, the reinforcing ribs of the connecting part define two pivot holes respectively, and a pivot extends through the pivot holes of said parallel portions and the pivot holes of said reinforcing ribs.

Claim 10 (original): The clip of claim 1, wherein said buckling piece is only linked to the cam member, and is not connected to the supporting portion.

Claim 11 (previously presented): A clip adapted to secure a heat sink to an electronic device, the clip comprising:

a main body comprising a pressing part adapted to press the heat sink to the electronic device, a first leg extending downwardly from one end of the pressing part, and a supporting portion extending from an opposite end of the pressing part;

a cam member located above the supporting portion, the cam member comprising a cam and a handle extending from the cam for rotating the cam, and

a buckling piece located below the supporting portion, the buckling piece comprising a connecting part moving up through the supporting portion to pivotally connect with the cam and a second leg extending from the connecting

Appl. No. 10/812,527
Amdt Dated Jan. 13, 2006
Reply to Office Action July. 11, 2005

part;

wherein the heat sink can be secured to the electronic device by rotating the cam to a locked position from an unlocked position, and the connecting part provides a spring finger which is located below the supporting portion at the unlocked and above the supporting portion at the locked position whereby the spring finger protects the pressing part from abruptly restored deformation.

Claim 12 (original): The clip of claim 11, wherein two reinforcing ribs extend downwardly from opposite longitudinal sides of the pressing part.

Claim 13 (original): The clip of claim 12, wherein a vertical thickness of each of the reinforcing ribs tapers from a center thereof to opposite ends thereof respectively.

Claim 14 (previously presented): The clip of claim 11, wherein said buckling piece is only linked to the cam member, and is not connected to the supporting portion.

Claim 15 (currently amended): A clip assembly comprising:

a main body defining an elongated pressing part ~~extending essentially along a first direction~~ with a first leg extending downwardly from one end of said pressing part;

a supporting portion located on the other end of the pressing part; and

an actuation combination including a cam member and a buckling piece,

Appl. No. 10/812,527
Amdt Dated Jan. 13, 2006
Reply to Office Action July. 11, 2005

the cam member essentially located on said supporting portion,
the buckling piece essentially located below the supporting portion and
defining a second leg opposite to said first leg,

a lower portion of the cam member pivotally, ~~along a pivotal axis,~~ linked to
an upper portion of the buckling piece,

said supporting portion defining a structure confining at least one of said
cam member and said buckling piece so as to prevent said actuation combination
from being dropped away from the main body while still allowing said
combination to be moveable relative to the main body in a range; wherein
neither the cam member nor the buckling piece is connected to the supporting
portion, and when said cam member is pivotally moved relative to the buckling
piece and said supporting portion, said buckling piece is up and down moved
relative to the supporting portion so as to perform a tension or relaxed manner
relative to a heat sink; ~~wherein~~

~~and the spring finger of the buckling piece is located above the supporting
portion or below the supporting portion correspondingly.~~

Claim 16 (previously presented): The clip assembly of claim 15, wherein
both said first leg and said second leg define locking means at lower ends thereof,
respectively.

Claim 17 (original): The clip assembly of claim 15, wherein said first leg is
integrally formed with the main body.